

RF SPLITTER (5-862MHz)



S2242A
2-Ways RF Splitter



S2244A
4-Ways RF Splitter

MODEL	FREQUENCY (MHz)	INSERTION LOSS (dB max.)	ISOLATION (dB min.)	RETURN LOSS (dB min.)	DIMENSION (mm)	WEIGHT (g)
S2242A 2-ways	5 ~ 47	3.7	16	16	58 x 48 x 23	35
	48 ~ 310	3.7	22	18		
	310 ~ 470	3.7	20	21.5		
	471 ~ 862	4	18	18		

MODEL	FREQUENCY (MHz)	INSERTION LOSS (dB max.)	ISOLATION (dB min.)	RETURN LOSS (dB min.)	DIMENSION (mm)	WEIGHT (g)
S2244A 4-ways	5 ~ 47	7.6	17	18	75 x 48 x 23	47
	48 ~ 310	7.6	20	18		
	310 ~ 470	7.6	20	17		
	471 ~ 862	8.5	13	13		

- High quality full band splitters for indoor use.
- Zinc die-casting housing with nickel plated.
- Particularly designed for easy mounting cable underpass.
- Built-in two grounding block.
- Screening efficiency meets CENELEC 50083-2:1998, Class B.
- All connectors are F-female, impedance 75 ohm.

Specifications are subject to change without notice.