

UBB TAP (5-2300MHz)



SSTV-H3284/10
4-Ways UBB Tap



SSTV-H3284/15
4-Ways UBB Tap

MODEL	FREQUENCY (MHz)	TAP LOSS (dB)	IN-OUT INSERTION LOSS (dB)	OUT-TAP ISOLATION LOSS (dB)	TAP-TAP ISOLATION LOSS (dB)	IN, OUT, TAP RETURN LOSS (Db)
SSTV-H3284/10 4-ways	5 ~ 40	10.5 ± 1	5	18	17	5
	40 ~ 450	10.5 ± 1.5	4.2	24	20	9
	450 ~ 1000	11.5 ± 1.5	5	20	18	10
	1000 ~ 1750	12.5 ± 1.5	5.7	20	18	8
	1750 ~ 2050	13 ± 1.5	6	18	16	8
	2050 ~ 2300	14 ± 2	6.5	18	15	8
DIMENSION (mm)		75 x 60 x 24				
WEIGHT (g)		103				
MODEL	FREQUENCY (MHz)	TAP LOSS (dB)	IN-OUT INSERTION LOSS (dB)	OUT-TAP ISOLATION LOSS (dB)	TAP-TAP ISOLATION LOSS (dB)	IN, OUT, TAP RETURN LOSS (Db)
SSTV-H3284/15 4-ways	5 ~ 40	15 ± 1.5	3	30	14	6
	40 ~ 450	15 ± 1.5	2.5	28	20	12
	450 ~ 1000	15 ± 1.5	3.5	23	20	10
	1000 ~ 1750	16 ± 2	4.5	20	18	9
	1750 ~ 2050	16 ± 2	5	20	17	8
	2050 ~ 2300	16 ± 3	5.5	20	17	8
DIMENSION (mm)		75 x 60 x 24				
WEIGHT (g)		103				

- Bandwidth 5MHz to 2.3GHz for VHF, UHF and satellite bands.
- IN to OUT power passing 24VDC 0.5A max.
- Available in all ports power pass.
- RFI shielded zinc die-casting housing with nickel plated.
- Particularly designed for easy mounting cable underpass.
- All ports are F-female connectors, impedance 75 ohm.

Specifications are subject to change without notice.